



FROM



PRODUCT OVERVIEW

QDI Stone Grip reduces slip and fall hazards on the smooth and slippery stone surfaces.

QDI Stone Grip anti Slip treatment is applicable for slippery dry or wet stone floors like, marble, granite, quartz, polished slabs terrazzo, terracotta, laterite, quarry tile, glazed brick, unsealed concrete & other mineral surfaces.

EFFECTIVENESS

QDI Stone Grip increases the coefficient of friction of the floor when it comes in contact with water / and or any type of moisture. However, the product can never completely exclude the possibility of people slipping in certain conditions.

2 year effective life is indicated and applies only if the product is applied and maintained as recommended by us.

QDI Stone Grip is not suitable for substrates that are not structurally sound or stable.

It is also not suitable for eliminating slipperiness due to oily or greasy substances.

IMPORTANT

Caution: Product suitability should be checked by first testing on a small inconspicuous area. When applied to polished or glazed surfaces there will be a loss of gloss depending on the quality / hardness of the Stones. Due to the nature of the product, avoid contact with metal, painted or lacquered surfaces. If this does occur, immediately wash off with water. Staining on metallic surfaces may occur. **DO NOT USE ON METALS.** Our instructions on this DS must be read and strictly observed before use!

FEATURES AND BENEFITS

1. Easy to use single pack product.
2. Coverage: Approx. 35 – 40 m2 per liter. (Depending upon marble porosity)
3. Quick to apply and treats the surface within 2 hours of application.
4. Low odour.
5. Nonflammable.
6. It may be used indoors and outdoors.

TECHNICAL DATA	
Density	Clear Liquid / 1.02
Coverage rate per liter	35 – 40 m2
Flammability	Nonflammable
Application	Internal / External
Dilution	Not recommended
Storage	Keep container tightly closed / below 30°C
Slip Test	ASM825A recommended



FROM



TESTING AND APPLICATION

1. The product is suitable for all types of natural Stones like marbles, granite etc.
2. It is very important before applying the product: First treat a small area so as to test the effect on the specific floor that is to be treated. This is because in some cases, the shine of the floor may be somewhat diminish.
3. If QDI Stone Grip is applied to a black or dark marble or granite, the stone may show a white bloom (This is known as the whitening effect. This disappears after a few weeks with maintenance / cleaning of the floor with a good degreaser.
4. Never apply QDI Stone Grip to a stone which has just been laid or installed. Leave a minimum of seven days before application.
5. Treat a maximum of 100 m2 at a time. For larger areas divide the floor into 100 m2 sections.
6. Never allow it to drip on the floor. If this happens repeat the application process again from the beginning following the instructions for use. This also applies if footprints are accidentally left on a floor undergoing the treatment.

MAINTENANCE AFTER TREATMENT

Once treated the floor must be clean with a good degreaser (soap free) cleaning agent. (The FSI Step 4 degreaser is a recommended product for this)

Always avoid the use of product containing soap. This may diminish the effect of the product.

DISCLAIMER

The consumer uses / orders the product on his/her own risk. In event of incorrect use and or failure to observe or follow the instructions & warnings on this DS, (which will be given to the customer before the works begin) the manufacturer / or supplier is not liable

The information in this DS is based on our experience and reports from customer's feedback. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason is given.